

16

BS EN 771-3:2011

Glencrete 7.3N Paint Grade

Category: II 440 x 100 x 215mm aggregate concrete masonry unit

Dimensions: 440 x 100 x 215mm

Dimensional tolerances:

Category: D1 Flatness: NPD

Parallelism: NPD

Configuration: Solid

Compressive Strength: Mean: 7.3N/mm²
Dimensional stability- moisture movement: <0.55

Shear bond strength: Fixed value: 0.15N/mm²

Flexural bond strength: NPD

Reaction to fire: Euroclass A1 Water absorbtion: NPD Water vapour permeability: EN1745: $5/15\mu$

Direct airborne sound insulation:

Gross dry density: 1910kg/m³ Configuration: As above

Thermal conductivity: 1.00W/mK int 1.15W/mK ext

Durability against freeze thaw: NPD
Dangerous substances: See note

Note: Information on dangerous substances will only be given

when and where required and in the appropriate form. See



16

BS EN 771-3:2011

Glencrete 10.4N Paint Grade

Category: II 440 x 100 x 215mm aggregate concrete masonry unit

Dimensions: 440 x 100 x 215mm

Dimensional tolerances:

Category: D1 Flatness: NPD

Parallelism: NPD

Configuration: Solid

Compressive Strength: Mean: 10.4N/mm²
Dimensional stability- moisture movement: <0.55

Shear bond strength: Fixed value: 0.15N/mm²

Flexural bond strength: NPD
Reaction to fire: Euroclass A1

 $\begin{tabular}{lll} Water absorbtion: & NPD \\ Water vapour permeability: & EN1745: 5/15 \mu \\ \end{tabular}$

Direct airborne sound insulation:

Gross dry density: 1910kg/m³ Configuration: As above

Thermal conductivity: 1.00W/mK int 1.15W/mK ext

Durability against freeze thaw: NPD
Dangerous substances: See note

Note: Information on dangerous substances will only be given

when and where required and in the appropriate form. See



16

BS EN 771-3:2011

Glencrete 7.3N Paint Grade

Category: II 440 x 140 x 215mm aggregate concrete masonry unit

Dimensions: 440 x 140 x 215mm

Dimensional tolerances:

Category: D1 Flatness: NPD

Parallelism: NPD

Configuration: Solid

Compressive Strength: Mean: 7.3N/mm²
Dimensional stability- moisture movement: <0.55

Shear bond strength: Fixed value: 0.15N/mm²

Flexural bond strength: NPD

Reaction to fire: Euroclass A1 Water absorbtion: NPD

Water vapour permeability: EN1745: 5/15µ

Direct airborne sound insulation:

Gross dry density: 1910kg/m³ Configuration: As above

Thermal conductivity: 1.00W/mK int 1.15W/mK ext

Durability against freeze thaw: NPD
Dangerous substances: See note

Note: Information on dangerous substances will only be given

when and where required and in the appropriate form. See



16

BS EN 771-3:2011

Glencrete 10.4N Paint Grade

Category: II 440 x 140 x 215mm aggregate concrete masonry unit

Dimensions: 440 x 140 x 215mm

Dimensional tolerances:

Category: D1
Flatness: NPD

Parallelism: NPD

Configuration: Solid

Compressive Strength: Mean: 10.4N/mm²
Dimensional stability- moisture movement: <0.55

Shear bond strength: Fixed value: 0.15N/mm² Flexural bond strength: NPD

Reaction to fire: Euroclass A1 Water absorbtion: NPD

Water vapour permeability: Direct airborne sound insulation:

> Gross dry density: 1910kg/m³ Configuration: As above

EN1745: 5/15μ

Thermal conductivity: 1.00W/mK int 1.15W/mK ext

Durability against freeze thaw: NPD
Dangerous substances: See note

Note: Information on dangerous substances will only be given

when and where required and in the appropriate form. See